

Garage Doors RollMatic

Roller garage door RollMatic, overhead garage door RollMatic OD ■ NEW

HÖRMANN





CONTENT

6 Good Reasons to Try Hörmann

12 Door Styles

16 Colour

20 Roller Garage Door RollMatic

25 External Roller Garage Door RollMatic

26 Overhead Garage Door RollMatic OD ■ **NEW**

30 Side Doors

32 Operator Accessories

36 Dimensions and Fitting Data

Some of the doors shown are equipped with optional extras and do not always correspond to our standard models.

The surface finishes and colours shown are subject to the limitations of the printing process and cannot be regarded as binding.

All rights reserved. No part may be reproduced without our prior permission.
Subject to changes.

◀ Roller garage door in White aluminium RAL 9006 and Hörmann aluminium entrance door ThermoSafe style 860 in White aluminium RAL 9006

Universally applicable

Roller garage doors and overhead garage doors open vertically and require minimum space inside the garage. This construction principle means you can make full use of the space inside and in front of the garage. The shape of the garage door opening is not of prime importance when fitting roller garage doors. Whether square, chamfered, with segmental or Norman arch – a Hörmann roller garage door always fits.

With the roller garage door RollMatic the ceiling remains free and can be used for lamps or as an additional storage space. The RollMatic is also available as an external roller garage door for fitting with low headroom and/or sideroom.

The overhead garage door RollMatic OD offers a minimum headroom and is ideally suited for modernisation in tight spaces.



▶ Roller garage door in Decograin Golden Oak



“A good reputation must be earned.”

August Hörmann


In keeping with the tradition started by the company’s founder, the Hörmann brand today is a true promise of quality. The family-owned company has over 80 years of experience in door and operator construction and, with sales of over 20 million doors, is no. 1 in Europe. This makes Hörmann roller garage doors and overhead garage doors a reassuring purchase.



1 Brand quality “Made in Germany”

All doors and operator components are developed and manufactured by Hörmann, are **perfectly matched** to each other and **tested and certified** by independent, recognised institutes to ensure your safety. They are manufactured in Germany according to the DIN ISO 9001 quality management system and meet the requirements of European standard 13241-1. Furthermore, our highly qualified employees work intensively on new products, continual further developments and improvements to details. The results are patents and one-of-a-kind products you can depend on.

Made in Germany





2 Garage doors for generations

Endurance tests under real conditions ensure mature series products with Hörmann quality. Thanks to this, excellent technical solutions and uncompromising quality assurance, you receive a **10-year warranty on all roller garage doors RollMatic and overhead garage doors RollMatic OD as well as 5 years on all Hörmann operators.***

* The complete warranty conditions can be found at: www.hormann.co.uk

3 An eye on the future

Hörmann is setting a good example. This is why the company obtains **100 % of its required energy from green sources.** At the same time, many tonnes of CO_2 are saved each year thanks to the introduction of an intelligent and certified energy management system. And last but not least, Hörmann also offers products for sustainable construction.





4 Reliable counterbalance

Only from Hörmann Roller garage door with tension spring assembly

A counterbalance system **integrated in the side guides** supports the operator during the opening and closing of the door and **prevents damage to the operator mechanism**.
The multiple spring assemblies and the double lifting cables prevent the door leaf from crashing to the floor in every position. In case of emergency, the door can be easily opened by hand. A crank handle is not necessary for this purpose for roller garage doors.

5 Reliable automatic safety cut-out

RollMatic doors are especially quiet and subject to minimum wear due to **the standard operators with soft start and soft stop**. The counterbalance system and the **reliable automatic safety cut-out** securely stops the door if it encounters an obstacle. For even more protection and safety, we recommend fitting a non-contact photocell.





6 Compact roller garage door

Roller garage doors RollMatic are the best choice if the **ceiling area of your garage** should remain **free** and if your garages are too small for a overhead garage door or sectional door. The door curtain **compactly winds up into the lintel** of the door opening, thus allowing you to use the ceiling for lamps or as an additional storage space.
The RollMatic is also available as an **external roller garage door for fitting in front of the opening** with low sideroom.

7 Space-saving overhead garage door

For garages with **a particularly low headroom**, overhead garage doors RollMatic OD are especially suitable. The door curtain is guided under the ceiling through narrow side guides. Due to the space-saving, lateral operator fitting the RollMatic OD has a **required headroom of only 60 mm.**



8 BiSecur radio system with certified security

Only from Hörmann

The bi-directional BiSecur radio system is based on **future-oriented technology** for the convenient and secure operation of garage and entrance gate operators, door operators, lighting and more. This extremely secure BiSecur encryption protocol, developed by Hörmann, with a stable, interference-free range makes sure that no-one can copy your radio signal. It was tested and certified by security experts at the Ruhr-Universität Bochum.

Watch the video at:
www.hormann.co.uk/videos

Perfectly matched and 100 % compatible

All BiSecur operators, receivers and control elements are 100 % compatible. Using a hand transmitter or radio code switch, for example, you can conveniently operate your garage door as well as an entrance gate equipped with a Hörmann operator, your door operators or other devices with BiSecur receivers. With our app * and Hörmann BiSecur gateway, you can conveniently control your Hörmann garage door or entrance gate operators, Hörmann entrance door** or the internal door operator PortaMatic as well as other devices using your **smartphone or tablet**.

* For smartphones or tablets with iOS or Android operating systems.

** To use this function it is required that your Hörmann entrance door ThermoCarbon / ThermoSafe is equipped with the automatic lock S5 / S7 Smart.





9 Convenient querying of the door position

You no longer have to go out in any wind and weather to check if your overhead garage door RollMatic OD is closed. At the press of a button, the colour of the LED on the HS 5 BS hand transmitter indicates the position of the door. If required, another push of a button*** closes the door. It is the most comfortable and secure way to control your door.

*** An additional photocell is required for operation without visual contact to the door.

10 Award-winning design

In addition to a black or white design, **BiSecur hand transmitters** are characterised by an elegant shape that fits easily in the palm of your hand.
Hörmann BiSecur hand transmitters with an optional high-gloss surface in a piano lacquer look have received the reddot design award for their exclusive design.

Watch the video at:
www.hormann.co.uk/videos

Figure above: Hand transmitter HS 5 BS with hand transmitter station (optional).

The perfect match for your home

To perfectly match your door to the architectural style of your home, we offer the roller garage door RollMatic and the overhead garage door RollMatic OD in various styles. For a natural door style, select one of the two timber designs of the Decograin or Decopaint surface finishes. For an especially elegant door style, we recommend the new colour Noir 2100 Sablé Anthracite Metallic. You can also select one of the 11 equally-priced colours – giving you more options for customisation. It goes without saying that we also offer matching side doors.



▶ Roller garage door in Decograin Golden Oak





▶ Roller garage door and side door in Traffic white RAL 9016





▼ External roller garage door Light grey RAL 7035






▲ Overhead garage door RollMatic OD
in Anthracite grey RAL 7016

◀ Roller garage door in Traffic white RAL 9016
and Hörmann aluminium entrance door
ThermoSafe style 413 in Traffic white RAL 9016

Harmonious overall appearance

The smooth surface of the aluminium profiles looks modern and elegant, unlike the ribbed profiles from other suppliers. Furthermore, a high-quality coating on the inside and outside of the door's surface makes it easy to clean. Only Hörmann offers you the complete door in the selected door colour without a surcharge. The door curtain, side guides, fascia panel, and shaft cover are thus combined in an attractive and harmonious unit. The hollow space of the profile is evenly filled with polyurethane rigid foam for quiet door travel.



Please note:

All colours are based on RAL.

The colours and surfaces shown are subject to the limitations of the printing process and cannot be regarded as binding. Please consult with your local Hörmann specialised dealer.

With respect to their technical properties and the paint system used all Hörmann roller garage doors correspond to the current state of the art. Pressure marks and abrasive wear are design-related and cannot be avoided. They do not impair the function and the durability of the roller garage door.

1 Profile view (concave side)
2 Profile view (convex side)

11 equally-priced colours


1 RAL 9016 Traffic white
2 RAL 9006 White aluminium
3 RAL 9005 Jet black
4 RAL 9001 Cream
5 RAL 8028 Terra brown
6 RAL 7035 Light grey
7 RAL 7016 Anthracite grey
8 RAL 6005 Moss green
9 RAL 5011 Steel blue
10 RAL 3003 Ruby red
11 RAL 1015 Light ivory

Glazing elements

Get more daylight in your garage! The glazing elements with synthetic panes are arranged across the entire profile width. The number of elements depends on the respective door width. A maximum of ten profiles can be fitted with glazings in each door.

Ventilation grilles

Ventilation of your garage improves the room climate and prevents mould. Ventilation grilles made of long-lasting plastic are arranged across the entire profile width. Each door can be equipped with a maximum of ten profiles.



1 Profile with synthetic glazing
2 Profile with ventilation grille

Decograin surface finish

The two Decograin decors in the colours Golden Oak and Rosewood have a convincingly real timber look. A special abrasion-resistant surface protection preserves the UV-resistant plastic film coating on the profiles over a long time.



Please note:

The colours and surfaces shown are subject to the limitations of the printing process and cannot be regarded as binding. Please consult with your local Hörmann specialised dealer.

Decograin decors





Roller garage door RollMatic

To create a uniform appearance, the side guides as well as the lintel and barrel casing are supplied in a matching Decograin decor. The Decograin surface finish is not available for external roller garage doors.





Overhead garage door RollMatic OD

The side guides and the fascia panel are powder-coated in the base colour of the decor.





1 Profile view (concave side) in brown
2 Profile view (convex side) in Decograin Golden Oak
3 Decograin Golden Oak
4 Decograin Rosewood
5 Side guide and profile in Decograin Golden Oak
6 Side guide and profile in Decograin Rosewood
7 Side guide in the base colour in Decograin Golden Oak
8 Side guide in the base colour in Decograin Rosewood

Decopaint surface finish


The Decopaint decors Golden Oak and Rosewood are an inexpensive alternative to Decograin surface finishes. The interior and exterior of the profiles are painted to look like timber. An elegant Anthracite Metallic paint is used for the colour Noir 2100 Sablé.



Decopaint decors








Roller garage door RollMatic / Overhead garage door RollMatic OD

The side guides, fascia panel and curtain cover are powder-coated in the base colour of the decor to create a harmonious appearance.







1 Profile view (concave side) in Decopaint Golden Oak
2 Profile view (convex side) in Decopaint Golden Oak
3 Decopaint Golden Oak
4 Decopaint Rosewood
5 Noir 2100 Sablé Anthracite Metallic
6 Side guide in the base colour of the decor
7 Side guide in the base colour of the decor
8 Side guide and profile in Noir 2100 Sablé Anthracite Metallic

Details perfectly matched to each other

The roller garage door RollMatic features a wide variety of innovative details with a single objective: providing you with security and comfort. From the particularly simple fitting through to the sophisticated safety patents, this concept runs through all aspects of the product.





Only from Hörmann Tension spring assembly



Only from Hörmann Wear-resistant bearing rings





1 A well-protected shaft

The standard shaft cover practically prevents reaching into the door barrel. In addition, it protects the curtain from damage and dirt when the door is open.
For coloured doors or doors with a Decograin surface finish, the cover matches the door curtain.
For Decopaint doors, the cover is supplied in the base colour of the door.

2 Tension spring assembly with multi-spring system

Hörmann RollMatic roller garage doors with double tension springs and double lifting cables protect the door leaf from crashing in every door position. The patented multi-spring system and the transparent protective cover prevent broken springs from flying out and thus protect from personal injury.

3 Wear-resistant bearing rings

The use of wear-resistant materials reduces marks of the bearing rings on the top door curtain profiles.

4 Standard wind locks

The Hörmann RollMatic roller garage doors can even withstand large wind loads (up to class 4). The wind locks fitted as standard in the profile ends keep the door securely within its guides. An additional advantage is increased break-in resistance.

5 Easy fitting

RollMatic roller garage doors can be fitted quickly and easily. The side guides, fascia panel and operator are bolted to the garage walls and lintel. The curtain is then pulled effortlessly onto the shaft by the operator and fixed via belts.

For more information, consult the technical manual under www.hormann.co.uk.

Standard operator, fitted outside of the cover for trouble-free maintenance

- With two HSE 4 BS hand transmitters
- Low power consumption
- Adjustable automatic timer**
- Standard emergency release via a pull cord



Control

- Separate housing with control buttons
- Integrated illumination



Hand transmitters HSE 4 BS textured surface black with plastic caps

Garage door operators	Standard operator
Pull and push force	650 N
Peak force	800 N
Max. opening speed	11 cm/s

* The complete warranty conditions can be found at: www.hormann.co.uk
** Photocell is required











Only from Hörmann Tension spring assembly

Optional extras

Optional emergency release from the outside 1

For garages without a second access door, we recommend the emergency release function allowing you to open your garage door from the outside in case of emergency (e.g. power failure).

Optional emergency battery 2

With this emergency power supply, you can bypass network power failures for up to 18 hours and max. 5 door cycles. The emergency battery recharges during normal operation.

Optional acoustic alarm 3

The shrill alarm sound with a volume of 110 db (A) effectively deters burglars.

Manually operated door with manual locking

Thanks to the supporting tension spring compensation, Hörmann roller garage doors can be easily opened and closed manually from the outside and inside. From the outside using the handle 4 and from the inside with a pull chain 5.
The manually operated roller garage door is mechanically locked using interior and exterior handles and a lock. Solid metal bolts extend on the right and left into the side guide.

Optional extras

Chamfered bottom profile

The solution for sloping ground: A chamfered aluminium bottom weather seal compensates for differences in height over the entire door width (max. 300 mm). The profile can be fitted without any difficulty. It is simply screwed onto the inserted curtain.
The bottom profile is delivered powder-coated in Jet black (similar to RAL 9005) as standard. On request, the bottom profile 1 is also available in a colour matching the door colour.

Additional fascia panel

The additional fascia panel 2 stabilises the fascia panel during fitting in the opening or behind the opening, if the fascia panel can be seen in the opening. It harmoniously covers the lintel without any unattractive fitting holes. The additional fascia panel is available in the colour of the door or with a Decograin surface.

Fitting compensation set

With uneven walls, the optional fitting compensation set 3 for flush door fitting can be applied. This is particularly advantageous for modernisations or timber structures.

For more information, consult the technical manual under www.hormann.co.uk.


1


2



3





1


2


3

External roller garage door

The solution for areas with a lack of interior sideroom

The RollMatic is also available as an external roller garage door for fitting in front of the opening if your garage has little lintel space and/or sideroom. The external roller garage door is supplied as a complete package with a matching operator. The side guides and the curtain cover come in the same colour as the door to create a uniform and harmonious appearance.

1 Variable operator positions

Depending on the fitting situation, operators for external roller garage doors can either be installed on the left or right. The shaft cover is 100 mm wider in this area and encloses the operator, protecting it from adverse weather effects or from unauthorised interference.

2 Tension spring cladding with vision sections

The vision sections in the spring cladding allow you to conveniently check whether the cable guide or springs are still functional. This gives you security even after many years of use.

3 Secured release


The operator can be easily released from the inside using a hand pulley. This allows you to open your door manually from the inside during a power failure, for example. Optionally, the secured release is also available for fitting to exterior walls in a lockable housing. For further information, please see page 23.

The space-saving garage door – ideal for modernisation

The narrow design of the overhead garage door RollMatic OD allows fitting in the garage even in very tight spaces.













1 Smooth door travel

Twin rollers evenly and smoothly guide the door curtain under the ceiling. The narrow aluminium side guides are connected by stable corner diversions with small radii. Due to this compact design the overhead garage door RollMatic OD only requires a lintel of 60 mm.

2 Sealed on all sides

The elastic lip seal in the lintel area and brush seals in the side guides optimally seal the door curtain. The flexible EPDM bottom profile compensates for unevenness in the floor and seals the bottom edge of the door.

3 Integrated counterbalance

The multiple spring assemblies optimally balance the weight of the door curtain in every position. This preserves the operator mechanism and, together with the automatic safety cut-out of the operator, guarantees safe door operation. In addition, the integral catch safety device protects the door against crashing to the floor in case of a possible cable tear.

4 Space-saving operator fitting

The operator booms can either be installed on the right or the left horizontal side guide. This compact design does not require additional headroom. (The illustration shows the optional SupraMatic operator.)

5 Variable fitting

The vertical side guides and the fascia panel are supplied in the colour of the door as standard. Thus the door can also be fitted partially or completely in the opening. Using the optional retrofit fascias 5, the door is fitted in the reveal and at the same time covers unattractive gaps in the lintel and opening areas. Additional brickwork and plastering work are no longer required.

ProMatic – the standard operator

- As standard with two 4-button hand transmitters HSE 4 BS
- Query of the door position with optional hand transmitter HS 5 BS
- Adjustable ventilation slot
- Automatic door locking





Standard hand transmitters HSE 4 BS, textured surface black with plastic caps

Garage door operators	ProMatic
Special feature	
Cycles per day /hour	12 / 5
Pull and push force	600 N
Peak force	750 N
Max. opening speed	14 cm/s
Max. door width	5000 mm
Max. door surface	11.25 m²

* The complete warranty conditions can be found at: www.hormann.co.uk

SupraMatic – the supra-fast operator with many additional functions

- As standard with one 5-button hand transmitter HS 5 BS and one HSE 4 BS
- Query of the door position
- Low power consumption
- Easy to program
- 2 × 7-segment display
- Adjustable ventilation slot
- Automatic door locking
- Operator cover made of brushed aluminium





Standard hand transmitters HS 5 BS, textured surface black



Standard hand transmitters HSE 4 BS, textured surface black with plastic caps

Garage door operators	SupraMatic E
Special feature	
Equipment	
Cycles per day /hour	25 / 10
Pull and push force	650 N
Peak force	800 N
Max. opening speed	22 cm/s
Max. door width	5500 mm
Max. door surface	13.75 m²

* The complete warranty conditions can be found at: www.hormann.co.uk

A matching side door for every RollMatic door

At Hörmann, side doors are given just as much consideration, as the overall appearance is only perfect if the side door matches the roller garage door. The side door NT 60 is thus available in all surface finishes and colours. The high-quality 60 mm aluminium frame construction is the ideal frame for the door infill and is fastened with glazing beads as standard.



External view



Interior view



Lever handle set as standard





For even more comfort

Hörmann operator accessories are characterised by innovative technology, exclusive design and 100 % compatibility – the ideal combination for everyone who values perfection.
You want maximum comfort?
We have the right control element for all your wishes and needs: elegant hand transmitters, stationary radio buttons or beautiful radio internal push buttons – choose your favourite.




HH ML 7516



Hand transmitter HS 5 BS
4 button functions
plus query button
1 High-gloss surface black
or white
2 Textured surface black



Hand transmitter HS 4 BS
4 button functions
3 Textured surface black

Hand transmitter HS 1 BS
1 button function
4 Textured surface black

Hand transmitter HSE 1 BS
1 button function
incl. eyelet for key ring
5 Textured surface black



Hand transmitter HSE 4 BS
4 button functions
incl. eyelet for key ring
6 Textured surface black
with chrome or plastic caps

Hand transmitter HSE 2 BS
2 button functions
incl. eyelet for key ring
7 High-gloss surface black
or white
8 High-gloss surface green,
purple, yellow, red, orange
9 Decors in silver, carbon,
dark rootwood

(Shown from left to right)





10 11

10 Hand transmitter HSD 2-A BS
Aluminium look,
2 button functions,
can also be used as a key ring

11 Hand transmitter HSD 2-C BS
High-gloss chrome,
2 button functions,
can also be used as a key ring



16

16 Radio code switch FCT 3 BS
For 3 functions,
with illuminated buttons



17

17 Radio code switch FCT 10 BS
For 10 functions,
with illuminated buttons
and protective cover



12

12 Hand transmitter HSP 4 BS
4 button functions,
with button lock-out
incl. key ring



13 14

13 Hand transmitter HSZ 1 BS
1 button function,
for insertion in vehicle
cigarette lighter

14 Hand transmitter HSZ 2 BS
2 button functions,
for insertion in vehicle
cigarette lighter



18

18 Radio finger-scan FFL 12 BS
For 2 functions
and up to 12 fingerprints



15

15 Radio internal push button FIT 2-1 BS
■ **NEW from autumn 2017**
For 2 functions
or 2 operators




19 20


Key switch
19 STUP 50
20 STAP 50
In a recessed version
and surface-mounted version
incl. 3 keys

Internal roller garage door

Fitting behind the opening, view of fitting side










Internal roller garage door


Fitting in the opening, interior view








Size range for internal and external roller garage door





Dimensions in mm

External roller garage door

Fitting in front of the opening, view of fitting side







Explanations

BMB	Ordering size width
BMH	Ordering size height
LB	Clear width
LH	Clear height
LDB	Clear passage width
LDH	Clear passage height
RAMB	Overall frame dimension width
RAMH	Overall frame dimension height
EBT	Fitting depth
S	Required headroom
SBH	Additional fascia panel height
OFF	Finished floor level
AUSS	Exterior

Fitting depth EBT

Up to 2300 mm door height	290 mm
From 2301 mm door height	335 mm

Required headroom S / additional fascia panel SBH

Up to 2300 mm door height	290 mm
From 2301 mm door height	335 mm

Clear passage LD

Height (with operator)	LH – 60 mm
Height (manually operated)	LH – 125 mm
Width	LB

Side space requirement	115 mm
External roller garage door operator side	215 mm

Wind load classes

Up to door widths of 3000 mm	Class 4
Up to door widths of 4500 mm	Class 3
Up to door widths of 5000 mm	Class 2

Water tightness under heavy rain	Class 2


X **External roller garage door cladding**
A symmetrical arrangement is also possible, in addition to a variable operator position (as standard on the left, optionally on the right) with projection of the shaft cover on the operator side.


* For a visually balanced look the barrel casing can be ordered symmetrically!


** At least 5 mm distance from fascia panel / side guide

Overhead garage door

Fitting behind the opening, view of fitting side










Overhead garage door

Fitting in the opening, interior view







Size range for overhead garage door RollMatic OD*


Clear height (LH)	Clear width (LB) 1000	1250	1500	1750	2000	2250	2500	2750	3000	3250	3500
3000											
2875											
2750											
2625											
2500											
2375											
2250											
2125											
2000											
1875											
1700											


* Flush-fitting in the opening with panel 95: max. LB 3150 mm, max. LH 2700 mm


Dimensions in mm

Overhead garage door

Flush-fitting in the opening with panel 95







Explanations


BMB	Ordering size width
BMH	Ordering size height
LB	Clear width
LH	Clear height
LDB	Clear passage width
LDH	Clear passage height
LMB	Structural opening width
RAMB	Overall frame dimension width
RAMH	Overall frame dimension height
LE	Distance back with operator
S	Required headroom
OFF	Finished floor level
AUSS	Exterior


Side space requirement	102 mm
Wind load class	Class 2
Water tightness under heavy rain	Class 2

Dimensions in mm

Side door with block frame


Fitting behind the opening,
opening inwards






Side door with block frame


Fitting in the opening,
opening inwards






Side door with block frame

Fitting in the opening,
opening outwards







Dimensions in mm

Side door with corner frame


Internal fitting,
opening inwards






Side door with corner frame

External fitting,
opening outwards





Explanations

BRB	Nominal size width
BRH	Nominal size height
BMB	Ordering size width
BMH	Ordering size height
LDB	Clear passage width
LDH	Clear passage height
LF	Structural opening
RAMB	Overall frame dimension width
RAMH	Overall frame dimension height
OFF	Finished floor level
AUSS	Exterior

Material

Door leaf frame and frame made of galvanized material, polyester powder-coated primer on both sides, with roller garage door section infill. Position of sections does not match the roller garage door RollMatic. Glazing and ventilation grilles arranged as in the roller garage door RollMatic.

Dimensions in mm


HÖRMANN

Experience Hörmann quality in new construction and modernisation

Hörmann provides an excellent basis for comprehensive planning. Carefully matched solutions offer you the very best in perfectly designed products for every area.

- **Garage doors**
  Optimally match your personal architectural style: up-and-over or sectional doors made of steel, grp or timber.
- **Gate and Door Operators**
  Enjoy extra convenience and break-in-resistant security with Hörmann operators for garage doors and entrance gates. You can profit from the convenience of Hörmann door operators in your residential space as well.
- **Entrance doors**
  Our comprehensive entrance door ranges include models that fit almost every need and requirement.
- **Steel doors**
  Sturdy doors for your entire home, from basement to roof.
- **Frames**
  Choose from our comprehensive range of products for new construction, expansion and modernisation.



Garage doors and entrance gate operators



Thermo65 / Thermo46 entrance doors



Steel doors

Hörmann: Quality without Compromise


Hörmann KG Amshausen, Germany


Hörmann KG Antriebstechnik, Germany


Hörmann KG Brandis, Germany


Hörmann KG Brockhagen, Germany


Hörmann KG Dissen, Germany


Hörmann KG Eckelhausen, Germany


Hörmann KG Freisen, Germany


Hörmann KG Ichtershausen, Germany


Hörmann KG Werne, Germany


Hörmann Alkmaar B.V., Netherlands


Hörmann Legnica Sp. z o.o., Poland


Hörmann Beijing, China


Hörmann Tianjin, China


Hörmann LLC, Montgomery IL, USA


Hörmann Flexon LLC, Burgettstown PA, USA


Shakti Hörmann Pvt. Ltd., India

Hörmann is the only manufacturer worldwide that offers you a complete range of all major building products from one source. We manufacture in highly-specialised factories using the latest production technologies. The close-meshed network of sales and service companies throughout Europe, and activities in the USA and Asia, make Hörmann your strong partner for first-class building products, offering “Quality without Compromise”.

GARAGE DOORS

OPERATORS

INDUSTRIAL DOORS

LOADING EQUIPMENT

HINGED DOORS

DOOR FRAMES

Issue 06.2017 / Print 09.2017 / HF 85900 EN-UK / PDF www.hoermann.com

Hörmann (UK) Ltd, Gee Road, Coalville, Leicestershire LE67 4JW
Phone (01530) 513000, Fax (01530) 513001

HÖRMANN